

SOILS

**THE TOUGHEST
PERFORMER**
«« FOR YOUR FIELD »»

30



HIGH LIFTING
CAPACITY

POWER PACKED
ENGINE

TWIN PROJECTOR
HEADLAMPS

AGRI, IND & TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH
YANMAR**

THE TOUGHEST
PERFORMER
«« FOR YOUR FIELD »»

S30

SOLIS



FEATURES	S 30
Model Description	SOLIS-30
ENGINE	
Engine Type	Mitsubishi Engine
HP Category	30
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	3000
Air cleaner	Dry with clogging Sencor
Max Torque (Nm)	82 Nm(±5%) 2000
Exhaust	Underhood Downdraft
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	17.06 Kmph (Varies with Tires)
Minimum Speed (Km/Hr)	1.82 Kmph (Varies with Tires)
BRAKES	
Brakes	Oil Immersed
Type of actuation	Mechanical
Parking Brake	Latch Type
DIFFERENTIAL LOCK	
Differential lock	Foot Operated
PTO	
PTO (rpm)	Rear 540 & 1000 RPM
PTO (actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 65Ah
Alternator	12V, 42Amp
HYDRAULICS	
3 point linkage	Cat 1-N
Stay Bars	Anchor Chain
Lifting Capacity	600Kg
Auxiliary hydraulic circuit	1DA/ 1SA (optional)
Lift rods	Standard

FEATURES	S 30		
Flow(LPM)	14.8		
SAFETY SWITCH			
Clutch Safety Switch	Standard		
CAPACITY (LTRS)(+/-5%)			
Fuel tank	26.5 L		
TURNING RADIUS			
Turning Radius (Meter)	2.7 with Brake 3.0 without Brake		
TYRE			
Front	7X14		
Rear	8.30-24		
DIMENSION & WEIGHT(+/-5%)			
Weight(kg)	1030		
Wheel Base (mm)	1570		
Total Length (mm)	2760		
Total Width (mm)	1165		
Height (mm) Up to ROPS	2000		
Min Ground Clearance (mm)	265		
Front Track (mm)	950		
Rear Track (mm)	870		
OTHER			
Trailer Hitch - Option 1	Standard		
- Option 2	E-Marked Swinging bar		
Front Tow Hook	Standard, Detachable		
TYRE COMBINATIONS			
Agricultural Front 6x12 Rear 8.3x20	Radial Agricultural Front 6.5/80-12 Rear 280/70 R18	Turf & Ind. Front 23x8.5-12 Rear 33x15.5-16.5	Ind. Galaxy Pro Front 220/55 R12 Rear 280/70 R16

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE. Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP



Metron

KEM Tower 15th Floor, Jl. Landasan Pacu Barat Blok B10 Kav. 2, Kota Baru Bandar Kemayoran, Jakarta Pusat 10610
Phone: +62 21 6570 4111 (Hunting) | Fax: +62 21 6570 4110 | Email: info@metronintercon.com

Jakarta | Surabaya | Medan | Pekanbaru | Padang | Jambi | Lampung | Palembang | Balikpapan | Banjarmasin | Pontianak | Sampit | Samarinda | Tarakan | Ketapang | Makassar | Manado | Kendari