

SINOTRUK



HOWO



HOWO **MINER**

HUANGHE 6X4 540HP MINING TRUCK



Model	ZZ595HV384KC3R	Model	ZZ595HV384KC3R
Engine (option 1)	Engine Model:WP13G530E310, Euro III emission standard Maximum output: 530 HP (390 kw) at 2100 rpm Displacement:11.596L Specific fuel consumption:189 g/kWh	Mesin (pilihan 1)	Model Mesin:WP13G530E310, standar emisi Euro III Kekuatan keluaran maksimum:530 HP (390 kw) pada 2100 rpm Isi Silinder:11.596L Konsumsi bahan bakar spesifik:189 g/kWh
Engine (option 2)	Engine Model:MC13.54-30, Euro III emission standard Maximum output: 540 HP (397 kw) at 1900 rpm Displacement:12.419L Specific fuel consumption:189 g/kWh	Mesin (pilihan 2)	Model Mesin:MC13.54-30, standar emisi Euro III Kekuatan keluaran maksimum:540 HP (397 kw) pada 1900 rpm Isi Silinder:12.419L Konsumsi bahan bakar spesifik:189 g/kWh
Transmission	Model FC6A250, automatic, 6 forward & 1 reverse, with PTO	Transmisi	Model Transmisi: FC6A250, otomatis, 6 Gigi Maju dan 1 Gigi Mundur, dengan PTO
Front Axle	loading capacity 25 tons; Drum brake	Aksel Depan	Kapasitas muatan 25 ton; rem tromol
Rear Axles	loading capacity 35 tons x 2; Drum brake; planetary reducer with double reduction; Differential lock between wheels and axles Ratio:17.62 18.385(optional)	Aksel belakang	Kapasitas muatan 35 ton x 2; rem tromol; peredam planet dengan reduksi ganda; Kunci diferensial antara roda dan aksel Rasio:17.62 18.385(optional)
Tyre	16.00R25	Ban	16.00R25
Dimensions (mm)	Wheel base: 3800+1750 Overall Dimensions (LengthxWidthxHeight): 9450x3650x4400	Dimensi (mm)	Jarak Poros: 3800+1750 Dimensi Keseluruhan (PanjangxLebarTinggi): 9450x3650x4400
Weight (kg)	Dead weight: 32000 Gross Vehicle Weight:95000	Berat (kg)	Berat Kosong: 32000 Berat Total (GVW): 95000
Performance	Maximum driving speed (km/h):45 Maximum gradeability (%): ≥35 Minimum ground clearance (mm):350 Minimum turning circle (m):11	Performa	Kecepatan maksimum(km/h): 45 Kemampuan tanjakan maksimum(%): ≥ 35 Jarak bebas ke tanah minimal(mm): 350 Radius putaran minimum(m): 11

SINOTRUK



HOWO - NX
6X4 TIPPER TRUCK

HOWO-NX 6X4 TIPPER TRUCK

HOWO NX 6X4 自卸车技术参数表
HOWO NX 6X4 tipper truck technical parameter table

Model	ZZ3257V404JF1	Model	ZZ3257V404JF1
Engine	Engine Model:MC11.36-50, Euro V emission standard Maximum output: 360 HP (268 kW) at 1900 rpm Displacement: 10.518L Specific fuel consumption: 186 g/kWh	Mesin	Model Mesin:MC11.36-50, standar emisi Euro V Kekuatan keluaran maksimum:360HP (268 kw) pada 1900 rpm Isi Silinder: 10.518L Konsumsi bahan bakar spesifik: 186 g/kWh
Transmission	Model HW19709XST, with synchronizer, 9 forward & 1 reverse ,with HW50 PTO	Transmisi	Model Transmisi: HW19709XST,synchromesh, 9 Gigi Maju dan 1 Gigi Mundur, HW50 PTO
Front Axle	VG95, 9.5 ton,drum brake	Aksel Depan	VG95, Kapasitas muatan 9.5 ton,rem drum
Rear Axles	MCX16ZG ,16 ton, drum brake Ratio:5.451	Aksel belakang	MCX16ZG, Kapasitas muatan 16 ton,rem drum Ratio:5.451
Tyre	11.00R20	Ban	11.00R20
Dimensions (mm)	Wheel base:4325+1350 Body Demision (Length x Width x Height): 6000×2300×1000+1000 Overall Dimension (LengthxWidthxHeight): 8125×2543×3160	Dimensi (mm)	Jarak Poros: 4325+1350 Ukuran Bodi (PanjangxLebarxTinggi):6000×2300×1000+1000 Dimensi keseluruhan(PanjangxLebarxTinggi): 8125×2543×3160
Weight (kg)	Dead weight:9500 Gross vehicle weight(GVW):41000	Berat (kg)	Berat Kosong: 9500 Berat Total(GVW): 41000
Performance	Maximum driving speed (km/h):65 Maximum gradeability (%): ≥30 Minimum ground clearance (mm):300 Minimum turning circle (m):11	Performa	Kecepatan maksimum(km/h): 65 Kemampuan tanjakan maksimum (%): ≥30 Jarak bebas ke tanah minimal(mm): 300 Radius putaran minimum(m): 11

The manufacturer reserves the right of technical alteration/change for better improvement without prior notice!



KEM Tower 15th Floor, Jl. Landasan Pacu Barat Blok B10 Kav. 2, Kota Baru Bandar Kemayoran, Jakarta Pusat 10610
Phone: +62 21 6570 4111 (Hunting) | Fax: +62 21 6570 4110 | Email: info@metronintercon.com

Jakarta | Surabaya | Medan | Pekanbaru | Padang | Jambi | Lampung | Palembang | Balikpapan | Banjarmasin | Pontianak | Sampit | Samarinda | Tarakan | Ketapang | Makassar | Manado | Kendari

SINOTRUK



HOWO 8X4 400HP DUMP TRUCK



Model	ZZ3317V4667B1R	Model	ZZ3317V4667B1R
Engine	<p>Engine Model:WP12.400E201, Euro II emission standard</p> <p>Maximum output: 400HP (294Kw) at 1900 rpm</p> <p>Displacement:11.596L</p> <p>Specific fuel consumption:193 g/kWh</p>	Mesin	<p>Model Mesin:WP12.400E201, standar emisi Euro II</p> <p>Kekuatan keluaran maksimum:400HP (294Kw) pada 1900 rpm</p> <p>Isi Silinder:11.596L</p> <p>Konsumsi bahan bakar spesifik:193 g/kWh</p>
Transmission	Model HW19709XST, with synchronizer, 9 forward & 1 reverse,with PTO	Transmisi	Model Transmisi: HW19709XST, synchromesh, 9 Gigi Maju dan 1 Gigi Mundur, dengan PTO
Front Axle	VGD95, loading capacity 9.5 tons×2; Drum brake	Aksel Depan	VGD95, kapasitas muatan 9.5 ton×2; rem tromol
Rear Axles	MCP16ZG, loading capacity 16 tons×2; Drum brake; planetary reducer with double reduction; Differential lock between wheels and axles Ratio:6.73	Aksel belakang	MCP16ZG, kapasitas muatan 16 ton×2; rem tromol; peredam planet dengan reduksi ganda; Kunci diferensial antara roda dan aksel Rasio: 6.73
Tyre	12.00R24	Ban	12.00R24
Dimensions (mm)	<p>Wheel base: 1800 + 4600 + 1400</p> <p>Overall Dimensions(LengthxWidthxHeight): 11750 x 2620 x 3800</p>	Dimensi (mm)	<p>Jarak Poros: 1800 + 4600 + 1400</p> <p>Dimensi keseluruhan(PanjangxLebarxTinggi): 11750 x 2620 x 3800</p>
Weight (kg)	<p>Dead weight: 14450</p> <p>Gross Vehicle Weight:51000</p>	Berat (kg)	<p>Berat Kosong: 14450</p> <p>Berat Total(GVW): 51000</p>
Performance	<p>Maximum driving speed (km/h):78</p> <p>Maximum gradeability (%): > 35</p> <p>Minimum ground clearance (mm):314</p> <p>Minimum turning circle (m):9.5</p>	Performa	<p>Kecepatan maksimum(km/h): 78</p> <p>Kemampuan tanjakan maksimum(%): > 35</p> <p>Jarak bebas ke tanah minimal(mm): 314</p> <p>Radius putaran minimum(m): 9.5</p>

The manufacturer reserves the right of technical alteration/change for better improvement without prior notice.

HOWO 8X4 400HP DUMP TRUCK



M Metron

KEM Tower 15th Floor, Jl. Landasan Pacu Barat Blok B10 Kav. 2, Kota Baru Bandar Kemayoran, Jakarta Pusat 10610
Phone: +62 21 6570 4111 (Hunting) | Fax: +62 21 6570 4110 | Email: info@metronintercon.com

Jakarta | Surabaya | Medan | Pekanbaru | Padang | Jambi | Lampung | Palembang | Balikpapan |
Bangarmasin | Pontianak | Sampit | Samarinda | Tarakan | Kerapang | Makassar | Manado | Kendari

 **SITRAK**



SITRAK **C7 6X4**

SITRAK C7 6X4



Model

ZZ4256V324HF1B

Engine

Engine Model:MC13.54-50,
Euro V emission standard Optional: Euro III
Maximum output:540hp(397Kw) at 2500 rpm
Displacement:12.419L
Specific fuel consumption:186 g/kWh

Transmission

Model ZF16S2531TO, with synchronizer,
16forward & 2 reverse,
with Hydraulic retarder and NH/1b PTO

Front Axle

VGD95, 9.5 ton, drum brake

Rear Axles

MCP16ZG, 16 ton, drum brake
Ratio:6.73

Tyre

12.00R24

Dimensions (mm)

Wheel base:3600+1415
Overall Dimensions(LengthxWidthxHeight):
7175X2513X3330

Weight (kg)

Dead weight:10600
Gross Combination Weight(GCW):120000

Performance

Maximum driving speed (km/h):70
Maximum gradeability (%):> 30
Minimum ground clearance (mm):186
Minimum turning circle (m):6

Model

ZZ4256V324HF1B

Mesin

Model Mesin:MC13.54-50,
standar emisi Euro V optional:Euro III
Kekuatan keluaran maksimum:
540HP (397 kw) pada 2500 rpm
Isi Silinder:12.419L
Konsumsi bahan bakar spesifik:186 g/kWh

Transmisi

Model Transmisi:ZF 16S2531 TO, synchromesh,
16 Gigi Maju dan 2 Gigi Mundur,
Retarder dan NH/1b PTO

Aksel Depan

VGD95, kapasitas muatan 9.5 ton,rem drum

Aksel belakang

MCP16ZG, kapasitas muatan 16 ton,rem drum
Rasio:6.73

Ban

12.00R24

Dimensi (mm)

Jarak Poros:3600+1415
Dimensi Keseluruhan (PanjangxLebarxTinggi):
7175X2513X3330

Berat (kg)

Berat Kosong:10600
Berat Kombinasi Kotor(GCW): 120000

Performa

Kecepatan maksimum(km/h):70
Kemampuan tanjakan maksimum(%):> 30
Jarak bebas ke tanah minimal(mm):186
Radius putaran minimum(m):6



C7H 6X6 480HP EURO5 TRACTOR



Model	ZZ4256V395MF1	Model	ZZ4256V395MF1
Engine	<p>Engine Model:MC13.48-50, Euro V emission standard</p> <p>Maximum output:480HP(353Kw) at 1900 rpm</p> <p>Displacement:12.419L</p> <p>Specific fuel consumption:185 g/kWh</p>	Mesin	<p>Model Mesin:MC13.48-50, standar emisi Euro V</p> <p>Kekuatan keluaran maksimum: 480HP (353 kw) pada 1900 rpm</p> <p>Isi Silinder:12.419L</p> <p>Konsumsi bahan bakar spesifik:185 g/kWh</p>
Transmission	<p>Model ZF16S2531TO, with synchronizer, 16forward & 2 reverse, with Hydraulic retarder and NH/1b PTO</p> <p>Transfer Case: GZ53P22 Ratio:0.981/1.583</p>	Transmisi	<p>Model Transmisi:ZF 16S2531 TO, synchronesh, 16 Gigi Maju dan 2 Gigi Mundur, Retarder dan NH/1b PTO</p> <p>Transfer Case: GZ53P22 Ratio:0.981/1.583</p>
Front Axle	MVP09, 9 ton, drum brake, Ratio:6.00	Aksel Depan	MVP09, kapasitas muatan 9 ton, rem drum, Rasio:6.00
Rear Axles	<p>MCP16ZG, 16 ton, Hub Reduction with inter axles differential lock</p> <p>Rasio:6.00 Optional:6.73</p>	Aksel belakang	<p>MCP16ZG, kapasitas muatan 16 ton, Hub Reduction dengan inter wheel & inter axles differential lock</p> <p>Rasio: 6.00 Optional:6.73</p>
Tyre	325/95R24	Ban	325/95R24
Dimensions (mm)	<p>Wheel base:3900+1400</p> <p>Overall Dimensions(LengthxWidthxHeight): 7555X2490X3425</p>	Dimensi (mm)	<p>Jarak Poros:3900+1400</p> <p>Dimensi Keseluruhan(PanjangxLebarxTinggi): 7555X2490X3425</p>
Weight (kg)	<p>Dead weight:11780</p> <p>Gross Combination Weight(GCW):100000</p>	Berat (kg)	<p>Berat Kosong:11780</p> <p>Berat Kombinasi Kotor(GCW): 100000</p>
Performance	<p>Maximum driving speed (km/h):86</p> <p>Maximum gradeability (%): 44</p> <p>Minimum ground clearance (mm):362</p> <p>Minimum turning circle (m):11</p>	Performa	<p>Kecepatan maksimum(km/h):86</p> <p>Kemampuan tanjakan maksimum(%):44</p> <p>Jarak bebas ke tanah minimal(mm):362</p> <p>Radius putaran minimum(m):11</p>

The manufacturer reserves the right of technical allocation change for better improvements without prior notice.

M Metron

KEM Tower 15th Floor, Jl. Landasan Pacu Barat Blok B10 Kav. 2, Kota Baru Bandar Kemayoran, Jakarta Pusat 10610
Phone: +62 21 6570 4111 (Hunting) | Fax: +62 21 6570 4110 | Email: info@metronintercon.com

Jakarta | Surabaya | Medan | Pekanbaru | Padang | Jambi | Lampung | Palembang | Balikpapan | Banjarmasin | Pontianak | Sampit | Samarinda | Tarakan | Ketapang | Makassar | Manado | Kendari

